

Industrial CCTV PoE Switch

- Industrial-level chip
- PoE management reset button
- Meet the requirements in extreme environment
- Uplink fiber&Ethernet ports
- 150m 100Mbps PoE+30W downlink ports
- Redundant power design



IP Transmission



Picture Model	Downlink Ports	Uplink Ports	Switch Capacity	Packet Forwarding Rate	PoE Standard	PoE Power Output	Surge / ESD	Working Temperature	Dimensions (L x W x H)
CCTV PoE Switch (VLAN, 250m/10Mbps, IEEE802.3af/at, 6KV)									
UTP7204E-POE-A1	4 x 10/100Base-TX PoE	1 x 10/100Base-TX 1 x 100Base-X SFP	1.2Gbps	0.89Mpps	802.3af/at	120W	6KV	-40°C~75°C	163 x 110 x 46.5(mm)
UTP7204GE-HPOE	4 x 10/100/1000Base-T PoE	2 x 10/100/1000Base-T 2 x 1000Base-X SFP(Combo)	14Gbps	10Mpps	802.3af/at, 60W PoE	120W	6KV	-40°C~75°C	163 x 110 x 46.5(mm)
UTP7208E-POE-A1	8 x 10/100Base-TX PoE	1 x 10/100/1000Base-T 1 x 1000Base-X SFP	5.6Gbps	4.2Mpps	802.3af/at	240W	6KV	-40°C~75°C	163 x 110 x 46.5(mm)
Layer 2 Web Management (Ports manage, VLAN, QoS, IGMP, SNMP, PoE Management, Trunk, RSTP)									
UTP7216E-POE-L2	16 x 10/100Base-TX PoE	2 x 10/100/1000Base-T 2 x 1000Base-X SFP	11.2Gbps	8.33Mpps	802.3af/at	270W	6KV	-10°C~50°C	442 x 255 x 44.5(mm)
UTP7224E-POE-L2	24 x 10/100Base-TX PoE	2 x 10/100/1000Base-T 2 x 1000Base-X	12.8Gbps	9.52Mpps	802.3af/at	390W	6KV	-10°C~50°C	442 x 255 x 44.5(mm)
UTP7516GE-POE-A1	16 x 10/100/1000Base-T PoE	2 x 10/100/1000Base-T 2 x 1000Base-X SFP	40Gbps	30Mpps	802.3af/at	270W	6KV	-10°C~50°C	442 x 305 x 44.5(mm)
UTP7524GE-POE-A1	24 x 10/100/1000Base-T PoE	2 x 10/100/1000Base-T 2 x 1000Base-X SFP	56Gbps	42Mpps	802.3af/at	390W	6KV	-10°C~50°C	442 x 320 x 44.5(mm)
UTP7524GE-MX	3 modules: 8 x 10/100/1000Base-T or 8 x 1000Base-X	2 x 10/100/1000Base-T 2 x 1000Base-X SFP	56Gbps	42Mpps	/	60W	6KV	-10°C~50°C	442 x 320 x 44.5(mm)

Products are subject to change without prior notice

OFFICE

Address : 5/F, Western Block, M-8 Building, Mid-section of Hi-tech Industrial Park, Nanshan District, Shenzhen, China
Tel : +86-755-83898016 Mobile: +86-15012669765
Fax : +86-755-83409500 Email : sales@utpvideo.com

FACTORY

Address : Fourth Floor, A2 Building, Founder Science & Technology Park, Baoan District, Shenzhen, China
Tel : +86-755-26785717



www.utepo.com

utpvideo-utepo

Industrial Fast-Ring Ethernet Switch



- Quick recovery of less than 20ms
- 60W PoE & compatibility of 802.3 af/at
- Level-4 industrial protection
- 10G SFP + uplink
- Support relay alarm for power off, network broken, PoE off
- High-reliability of 6KV lightning protection



IP Transmission



Picture Model	Downlink Ports	Uplink Ports	Switch Capacity	Packet Forwarding Rate	PoE Standard	PoE Power Output	Surge / ESD	Working Temperature	Dimensions (L x W x H)
UTP7308GE	8 x 10/100/1000Base-T	4 x 1000Base-X	24Gbps	17.86Mpps	/	/	6KV	-40°C~75°C	163 x 110 x 46.5(mm)
UTP7308GE-POE	8 x 10/100/1000Base-T PoE	4 x 1000Base-X	24Gbps	17.86Mpps	802.3af/at 60W	270W	6KV	-40°C~75°C	163 x 110 x 46.5(mm)
UTP7304GE	4 x 10/100/1000Base-T	2 x 1000Base-X	12Gbps	11.9Mpps	/	/	6KV	-40°C~75°C	163 x 110 x 46.5(mm)
UTP7304GE-POE	4 x 10/100/1000Base-T PoE	2 x 1000Base-X	12Gbps	11.9Mpps	802.3af/at+ 60W	150W	6KV	-40°C~75°C	163 x 110 x 46.5(mm)
UTP7524GE-POE-4GF	24 x 10/100/1000Base-T PoE	4 x 1000Base-X	56Gbps	41.66Mpps	802.3af/at	390W	6KV	-10°C~50°C	442 x 320 x 44(mm)
UTP7516GE-POE-4GF	16 x 10/100/1000Base-T PoE	4 x 1000Base-X	40Gbps	29.76Mpps	802.3af/at	270W	6KV	-10°C~50°C	442 x 320 x 44(mm)
UTP7624GE-L3	24 x 10/100/1000Base-T	4 x 10GBase-X	128Gbps	95.23Mpps	/	/	6KV	-10°C~50°C	442 x 320 x 44(mm)
UTP7624GE-POE-L3	24 x 10/100/1000Base-T PoE	4 x 10GBase-X	128Gbps	95.23Mpps	802.3af/at	390W	6KV	-10°C~50°C	442 x 320 x 44(mm)



National High-Tech Enterprise

ISO9001

Shenzhen Golden Brand

CCTV PoE Switch

- One key CCTV (Man, 250m)
- 6KV surge protection
- POE management and power alarm indication
- IEEE 802.3af/at international standard
- Flat-pin RJ45 connector design




PoE Extender PoE Injector PoE Splitter

- Conversion efficiency ≥90%
- IEEE 802.3af/at international standard
- Network connectors adopt high-power PoE flat-pin RJ45 ports with 30u gold-plated
- Industrial fast-ring network switch series



IP Transmission



Picture Model	Downlink Ports	Uplink Ports	Switch Capacity	Packet Forwarding Rate	PoE Standard	PoE Power Output	Surge / ESD	Working Temperature	Dimensions (L x W x H)
CCTV PoE Switch (VLAN, 250m/10Mbps, IEEE802.3af/at, 6KV)									
UTP3-SW04-TP60	4 x 10/100Base-TX PoE	2 x 10/100Base-TX	1.2Gbps	0.89Mpps	802.3af/at	60W	6KV	-10℃~55℃	135 x 86 x 27(mm)
UTP3-GSW04-TP60	4 x 10/100/1000Base-T PoE	2 x 10/100/1000Base-T	12Gbps	8.9Mpps	802.3af/at	60W	6KV	-10℃~55℃	135 x 86 x 27(mm)
UTP3-SW08-TP120	8 x 10/100Base-TX PoE	1 x 10/100Base-TX	1.8Gbps	1.34Mpps	802.3af/at	120W	6KV	-10℃~55℃	200 x 102 x 27(mm)
UTP3-SW08-TP120-A1	8 x 10/100Base-TX PoE	2 x 10/100/1000Base-T	5.6Gbps	4.2Mpps	802.3af/at	120W	6KV	-10℃~55℃	200 x 102 x 27(mm)
UTP3-GSW0802-TP120	8 x 10/100/1000Base-T PoE	2 x 10/100/1000Base-T	20Gbps	14Mpps	802.3af/at	120W	6KV	-10℃~55℃	200 x 102 x 27(mm)
UTP3-GSW0802-TSP120	8 x 10/100/1000Base-T PoE	1 x 10/100/1000Base-T 1 x 1000Base-X SFP	20Gbps	14Mpps	802.3af/at	120W	6KV	-10℃~55℃	200 x 102 x 27(mm)
PoE Web Management Switch (PoE Management, PoE Power alarm indication, VLAN, IEEE802.3af/at, 6KV)									
UTP31-SW16-TP300	16 x 10/100Base-TX PoE	2 x 10/100/1000Base-T 1 x 1000Base-X SFP(Combo)	7.2Gbps	5.3Mpps	802.3af/at	270W	6KV	-10℃~55℃	442 x 285 x 44.5(mm)
UTP31-SW24-TP420	24 x 10/100Base-TX PoE	2 x 10/100/1000Base-T 1 x 1000Base-X SFP(Combo)	8.8Gbps	6.55 Mpps	802.3af/at	390W	6KV	-10℃~55℃	442 x 285 x 44.5(mm)
UTP3-GSW2404-TSP200	24 x 10/100/1000Base-T (16 Port PoE)	2 x 10/100/1000Base-T 2 x 1000Base-X SFP	52Gbps	38Mpps	802.3af/at	180W	6KV	-10℃~55℃	442 x 285 x 44.5(mm)
UTP3-GSW2404-TSP420	24 x 10/100/1000Base-T PoE	2 x 10/100/1000Base-T 2 x 1000Base-X SFP	52Gbps	38Mpps	802.3af/at	390W	6KV	-10℃~55℃	442 x 285 x 44.5(mm)
Layer 2 Web Management Switch (VLAN, Qos, IGMP, Snmp, PoE Management, Trunk, RSTP, IEEE802.3af/at, 6KV)									
UTP3-SW16-TP300	16 x 10/100Base-TX PoE	2 x 10/100/1000Base-T	7.2Gbps	5.3Mpps	802.3af/at	270W	6KV	-10℃~55℃	442 x 224 x 44.5(mm)
UTP3-SW24-TP420	24 x 10/100Base-TX PoE	2 x 10/100/1000Base-T	8.8Gbps	6.55Mpps	802.3af/at	390W	6KV	-10℃~55℃	442 x 224 x 44.5(mm)

IP Transmission



Picture Model	Medium	Distance	Rate	PoE Standard	Surge	Working Temperature	Dimensions (L x W x H)
UTP7301EOC	Coaxial Cable	1200m	10/100M	/	2KV	-10℃~55℃	63.2 x 82 x 25(mm)
	Cat5/5e/6	700m					
UTP7301EPOC	Coaxial Cable	500m	10/100M	802.3af/at	2KV	-10℃~55℃	63.2 x 82 x 25(mm)
	Cat5/5e/6	400m					
UTP7301EOC-A1	Coaxial Cable	1200m	10/100M	/	2KV	-10℃~55℃	63.2 x 82 x 25(mm)
	Cat5/5e/6	700m					
UOF7201GE	Fiber	20km	10/100M	/	6KV	-40℃~75℃	103 x 82 x 25(mm)
UTP7201ER-POE	Cat5/5e/6	300m	10/100M	802.3af/at	2KV	-40℃~75℃	103 x 82 x 25(mm)
UTP3-VMC01-POE	Fiber	20km	10/100M	802.3af/at	2KV	-10℃~55℃	113 x 45.5 x 29(mm)
UTP3-VER01-POE	Cat5/5e/6	100m	100M	802.3af/at	2KV	-10℃~55℃	113 x 45.5 x 29(mm)
Picture Model	Housing	PoE Power	Rate	PoE Standard	Surge	Working Temperature	Dimensions (L x W x H)
UTP7201GE-PSE30	ABS Plastic	30W PSE	10/100/1000M	802.3af/at	6KV	-10℃~50℃	160 x 64 x 60(mm)
UTP7201GE-PSE60	ABS Plastic	60W PSE	10/100/1000M	802.3af/at	6KV	-40℃~75℃	160 x 64 x 60(mm)
UTP7201GE-PD25	Aluminum-alloy	25W PD	10/100/1000M	802.3af/at	6KV	-10℃~50℃	82 x 63 x 25(mm)
UTP3-PDA01-B13W	ABS Plastic	13W PD	10/100M	802.3af/at	2KV	-10℃~50℃	260 x 36 x 26(mm)