
5.8G 900Mbps Security Exclusive Outdoor CPE







Overview

The CP5-1200 is a 5.8GHz long distance wireless transmission devices with up to 867Mbps throughput capacity, of which the transmission distance is up to 20km at a stable wireless coverage to ensure the perfect using experience of clients. Equipped with IP67 protection enclosure, featuring with anti-surge, mould proof & antiseptic, it ensures the stable operation in the harsh environment.

Application



Board Diagram



Specification -

Model	CP5-1200	
Main Chip	IPQ4028	
Wireless Technology	5.8G:867Mbps, 802.11a/n/ac	
Operating Frequency	5180~5320MHz , 5745~5825MHz (Support extend of 4920~6100MHz)	
Antenna	23dBi directional antenna Horizontal angle: 11 degree, vertical angle: 11 degree.	
Output Power	27dBm	
Receiving Sensitivity	-96dBm@6Mbps , -85dBm@MCS0	
Transmission Rate	11n : 300Mbps 11ac : 867Mbps	
Power	802.3 at 48V PoE+	
Interface	1*10/100/1000 Mbps auto-sensing RJ45 ports	
Operation Temperature	-40°C ~ 65°C	
Storage Temperature	-40°C ~ 80°C	
Operation Humidity	5%~95%RH Non-condensing	
Dimension	Φ372mm×241mm	
Weight	0.9kg	
Networking Mode	Routing / Bridge	
Wireless Mode	Access point, client, WDS access point, WDS client.	
Security Mechanism	IP/MAC address filtering, hidden network name	
Network Protocol	TCP/UDP/ARP/ICMP/DHCP/HTTP/NTP	
ACK timing	Support (automatically adapt to changes in transmission distance)	
System	NTP , Syslog , SNMP , AC	
Configuration Management	Support web configuration, AC remote configuration and SNMP management	
Update	Support firmware web update Default IP: 192.168.1.36 Username/Password: admin/admin	
Flexible Bandwidth Configuration	10M/20M/40M/80MHz	

Packing List

CONTENT	QTY
CPE	1
POE Power Supply	1
Mounting Kits	1
Cable	1
User Manual	1

Related Product

NAME	MODEL
2.4G 300M Elevator Exclusive CPE	CP2-300
5.8G 300M Security Exclusive Outdoor CPE	CP5-900